

# EPSON® EpsonNet 10/100 Base Tx External

- Reliable high speed 10/100 Base Tx external printserver
- Easily connects to inkjet printers via USB
- Stylish and discreet silver design
- Includes EpsonNet tools for complete network management
- Antitheft slot for added security
- Compatible with standard network environments: Windows®, NetWare, AppleTalk®, Macintosh®



## *Simple printer networking for the home or office*

Improve your home or office network and make life easier with an EpsonNet Print Server.

For anyone using more than one inkjet printer in the office you will understand the need for an easy to use, easy to install Print Server.

With simple USB connections, the EpsonNet Print Server is the answer you have been looking for. Whether creating a small home network or giving

you and your staff the freedom to simply click the pre-installed icon on your desktop, you will be able to select the best printer needed for the job.

The EpsonNet Print Server enables printers in different locations to be used by anyone connected to the network helping to free up space normally taken up by individual desktop printers.

# EPSON® EpsonNet 10/100 Base Tx External

## How did you ever get by without one?

Easy to set-up and use, you'll be enjoying the EpsonNet Print Server within minutes of taking it out of the box. Using simple USB connections, the EpsonNet Print Server can be set-up in moments and is configured quickly and easily on-screen, using the EpsonNet tools provided.

The EpsonNet Print Server will blend nicely into your home or office with its compact, discreet and stylish silver design. It is fast too, transferring data at 10 and 100 Mbps (megabits per second) to give you the same speed you'd expect from other ethernet devices.

If you are familiar with network operation, you'll be pleased to know the EpsonNet Print Server is completely manageable through network tools. Use the EpsonNet Assist family (Windows®, Macintosh® or web-based) to set and control all your network printer settings and use the EpsonNet WebManager to supervise and monitor all the printers on the network.

Where you place your EpsonNet Print Server is entirely up to you. Make a spectacle of it by using the included auxillary stand to secure it to a work surface, or stow it away out of sight and wall mount it. If you're installing it in an open office and are concerned about security, the EpsonNet Print Server also features an antitheft slot with which it can be firmly secured in place.



## Specifications

PART NUMBERS	Europe countries: C12C824023 UK: C12C824025
GENERAL FEATURES	10/100 Base Tx external print server 2 USB connectors 2 LED indicators EpsonNet Win/Mac/WebAssist for easy configuration EpsonNet WebManager for management EpsonNet Direct Print and Internet print for printing under windows
SUPPORTED PERIPHERALS	Network capable USB base peripherals (not equipped with TypeB Slot) Inkjet: EPSON Stylus COLOR 760/880/980/1160, EPSON Stylus C63/C64/C83/C84/C80, C82, EPSON Stylus Photo 870/890/950/ 1270/1280/1290/2000P/2100/2200/2300/900/960 Multifunction devices: EPSON Stylus CX5100/5200/Stylus CX3100/3200 Dot Matrix: LQ-630 Network Type: Ethernet 100 Base Tx and Ethernet 10BaseT Data Rate: 10 Mbps and 100 Mbps
COMPATIBLE NETWORK PROTOCOLS	TCP/IP: ARP, RIP, ICMP, IGMP, UDP, TCP, LPR, LPD, FTP, NetBIOS/SMB, RARP, TELNET, DHCP/BOOTP/APIPA, Port 9100/2501, IPP HTTP SNMP, ENPC, SSDP Microsoft Windows™: NetBIOS over TCP/IP and over NetBEUI, SNMP and ENPC over NetBEUI NetWare: IPX, SPX, NCP, RIP,SAP, NDS IP SNMP,ENPC AppleTalk: ELAP, AARP, DDP, NBP, ZIP, RTMP, ATP, PAP, ENPC, SNMP
APPLICATION SERVICES	D-DNS
DIMENSION	100 (W) x 151 (D) x 160 (H) mm (with rotary stand) 43 (W) x 151 (D) x 160 (H) mm (without rotary stand)
WEIGHT	0.5kg for main unit only
ENVIRONMENTAL RANGES	Temperature in operation: 10°C-40°C Temperature in non-operation: -30°C-60°C Humidity in operation: 15% -85% RH Humidity in non-operation: 5%-95% RH Vibration in operation: 0.15 G, 5-55 Hz x, y, z directions Vibration in non-operation: 0.5 G, 5-55 Hz x, y, z directions Impulse: 1 G
POWER REQUIREMENTS	100-240 Volts 50/60 Hz
PRODUCT CERTIFICATION	CE Marketing EN 55022 Class B EN 55024 EN 50082-1 EN 61000-3-2 EN 61000-3-3 EN 301 489-17
WHATS IN THE BOX	EpsonNet 10/100 Base Tx external print server, AC cable, AC adapter, multilingual CD ROM (utilities and on-line manuals), various documents (setup guide)

EPSON Europe B.V.  
Entrada 701  
1096 EJ Amsterdam  
The Netherlands.  
Telephone: +31 (0)20 3145 000  
Home Page: [www.epson-europe.com](http://www.epson-europe.com)

ISO 14001 BVQI Certification Number 80679

